



ScandJubilee SSP 754 K2

ScandJubilee is a very smooth, white calendered woodfree paper with a finish suitable for coloured toner based, ink-jet and most printing ink processes.

A versatile paper, ScandJubilee has been shown to give a particularly good overprinting performance with colour laser printers, digital colour photocopier and colour ink-jet machines.

ScandJubilee can also give excellent offset lithographic printing results for an uncoated paper.

Care is required to select pre-printing inks suitable for laser/copier print processes and overprinting directly onto pre-print needs to be treated with caution, to ensure satisfactory toner key or ink-jet drying time.

When pre-printing laminate intended for subsequent overprinting, care must be taken to control the laminate moisture and curl. Failure to do so can lead to feed and print problems particularly in laser and copier systems.

Care also needs to be taken during storage and conversion.

We would advise that self adhesive laminates should be fed from the printer manufacturer's recommended input which, for desktop printers, is usually a multipurpose feed tray.

Face Material Properties

Grammage	73 g/m ²	ISO 536
Caliper	71 microns	ISO 534
Smoothness (Bendtsen)	30 ml/min	ISO 8791/2

Adhesive

SSP 754 Permanent

ScandStick 754 is a high tack adhesive that performs well on a wide range of surfaces, including various boards.

754 gives very good adhesion to low energy surfaces such as polythene, both at room temperature and under chill conditions.

Suitable for use with ink-jet, laser and other variable information printable laminates, 754 has excellent resistance to edge bleed to prevent contamination inside printers.

It is recommended that products produced with 754 and destined for laser toner fusion work should be waste-trimmed on the edges.

Note: Not advised for labelling highly plasticised materials, eg: Flexible PVC.

Composition	rubber based hot melt	
Minimum Application Temperature	0 °C	
Service Temperature	-15 to +75 °C	
Food contact	Meets composition requirement of indirect food additives regulation FDA 21-CRF 175-105	

Backing

ScandSil Kraft 74 (K2) is a bleached kraft backing with good lay-flat properties and dimensional stability.

Caliper	78 ±5 microns	ISO 534
Translucency	n/a	ISO 2469

Laminate

Laminate Shelf Life	24 months stored at 20°C/50% RH
Typical Laminate Caliper	167 ±15 microns

Food Packaging Applications: The adhesive raw materials are listed under European/US food packaging regulations (BgVV XIV or FDA 21 175.105) and are safe for use in limited contact with foodstuffs.

Toy and Packaging Regulations: The materials used have been tested and comply with the current heavy metals regulations EN71-3 Safety of Toys and the UK Packaging (Essential Requirements) Regulations 1998.

ScandJubilee SSP754 K2
Revision: 07-01-29 101002LON000

page 1 of 1
Replaces all previous information.

Self Adhesive Roll Products

ScandStick AB Box 22103 25023 Helsingborg Sweden Tel +4642250050 Fax +4642250090 The values indicated in this leaflet are not intended to be a specification but a guide to the values that may generally be expected. Customers should independently determine, prior to use, the suitability of any material for a specific purpose. All information is subject to change without notice.