



ScandPrint V PB

SSP 713 x 2

HG0 x 2

ScandPrint V is a versatile white calendered woodfree paper, specially selected for use in both simple primary label applications and thermal transfer overprinting.

The surface is suitable for solids, sharp halftones and clear text including small type faces by traditional print methods.

ScandPrint V may also be used as suitable media for most thermal transfer bar code label printers and print and apply label applicators, with suitable wax or wax/resin ribbons.

ScandPrint V has both high smoothness to give an even transfer of ink from the ribbon to the paper and suitable absorbency to allow excellent ink key and smudge resistance.

NOTE: This is a **PiggyBack** construction that has two release coated backing papers, two layers of adhesive and a face material which allows a label to be applied, complete with backing, for future or further application.

Face Material Properties

Basis weight	73 ± 3 g/m ²	ISO 536
Caliper	72 ± 4 microns	ISO 534
CIE whiteness	147 %	ISO 11475
Opacity	87 %	ISO 2471

Adhesive

SSP713 General purpose permanent

SSP713 has excellent initial tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates.

Particularly good adhesion to cardboard, plastic and glass.

Note: Not advised for labelling highly plasticised materials, eg: flexible PVC

Composition	rubber based hotmelt
Minimum Application Temperature	8 °C
Service Temperature	-10 to +70 °C
Food contact	ISEGA certified approved for direct contact with dry and moist non-fatty foods. Complies with FDA175.105, BfR XIV.

Backing

HG0 honey glassine backing allows high speed conversion and consistent dispensing on a wide range of equipment.

Caliper	49 ± 3 microns	ISO 534
Transparency	50 %	ISO 2469

Laminate

Laminate Shelf Life	12 months stored at 20°C/50% RH
Typical Laminate Caliper	189 ± 20 microns

Food Packaging Applications: The adhesive raw materials are listed under European/US food packaging regulations (BgVV XIV or FDA 21 175.105) and are safe for use in limited contact with foodstuffs.

Toy and Packaging Regulations: The materials used have been tested and comply with the current heavy metals regulations EN71-3 Safety of Toys and the UK Packaging (Essential Requirements) Regulations 1998.

ScandPrint V PB SSP713 HG0
Revision: 210312P

page 1 of 1
Replaces all previous information

Self Adhesive Roll Products

ScandStick AB Box 25 S-263 21 Höganäs Sweden Tel +4642250050 Fax +4642250090 The values indicated in this leaflet are not intended to be a specification but a guide to the values that may generally be expected. Customers should independently determine, prior to use, the suitability of any material for a specific purpose. All information is subject to change without